

70 (2007 - ) : with AFS (Active Front Steering) : 1 Axle Air Suspension : Sport Suspension : 20" Wheel

**Front : Left**

Actual	Before	Specified Range
-0.5°	-0.5°	-0.7° 0.0°
0.12°	0.18°*	0.03° 0.13°
		8.8° 9.8°
		8.1° 9.8°
		-2.60° -1.60°

**Front : Right**

Actual	Before	Specified Range
0.0°	0.0°	-0.7° 0.0°
0.05°	0.15°*	0.03° 0.13°
		8.8° 9.8°
		8.1° 9.8°
		-2.60° -1.60°

Camber  
Caster  
Toe  
SAI  
Included Angle  
Turning Angle Diff.

**Front**

Cross Camber  
Cross Caster  
Cross SAI  
Total Toe  
Cross Turn Diff.

Actual	Before	Specified Range
-0.5°*	-0.5°	-0.5° 0.5°
		-0.5° 0.5°
0.17°	0.32°*	0.07° 0.27°

**Rear : Left**

Actual	Before	Specified Range
-1.6°	-1.8°*	-1.8° -1.3°
0.06°	0.04°	0.00° 0.17°

**Rear : Right**

Actual	Before	Specified Range
-1.6°	-1.6°	-1.8° -1.3°
0.10°	0.10°	0.00° 0.17°

Camber  
Toe

**Rear**

Cross Camber  
Total Toe  
Thrust Angle

Actual	Before	Specified Range
0.0°	-0.1°	
0.17°	0.14°	0.00° 0.33°
-0.02°	-0.03°	-0.07° 0.07°

\* This value is not within specification. Tire wear, handling and safety problems may result.