

## Automatic transmission fluid (yellow)

**febi no. 14738 (1 litre)**  
**febi no. 29738 (5 litres)**  
*e.g. repl. no. G 052 162 A2*

febi 14738 is a high-grade automatic transmission fluid with long-term properties for extended oil change intervals.

- The basis of this semi-synthetic oil are high-grade base oils and special additives which are specifically matched in their composition for use in automatic transmissions and lock-up clutches.



### Recommended applications

• BMW 83 22 9 404 328	• VOITH G 1363
• BMW/Mini 83 22 9 407 858	• VW/Audi G 052 162 A2
• Jaguar JLM 20238	• VW LT 71141 (ESSO)
• Peugeot 9736.22	• VW TL 521 62
• MB 236.11 (001 989 22 03)	• ZF TE-ML 11B, 14B
• VOITH G 607	

Properties	Unit	Test method
Viscosity at 40° C	37 mm <sup>2</sup> /s	DIN 51562-T1
Viscosity at 100° C	7.4 mm <sup>2</sup> /s	DIN 51562-T1
Density at 15° C	855 kg/m <sup>3</sup>	DIN EN ISO 12185
Flash point	219 ° C	DIN ISO 2592
Pour point	-54 ° C	DIN ISO 3016

## Automatic transmission fluid (yellow)

**febi no. 34608 (1 litre)**  
*e.g. repl. no. G 055 005 A2*

febi 34608 is state-of-the-art automatic transmission fluid, specially developed for use in ZF 6-speed automatic gearboxes.

- ZF 6HP19
- ZF 6HP19X (ex. Audi Q7)
- ZF 6HP21
- ZF 6HP21X
- ZF 6HP26
- ZF 6HP26X
- ZF 6HP26A61 (ex. Audi W12)
- ZF 6HP28
- ZF 6HP28X
- ZF 6HP28A61
- ZF 6HP32
- ZF 6HP32A
- ZF 6HP32X

The vehicle manufacturers' change intervals must be adhered to!



### Recommended applications

• BMW 83 22 0 144 137	• Land Rover TYK500050
• BMW 1375.4	• VW/Audi G 055 005 A1/A2/A6
• BMW 83 22 0 142 516	• ZF gearboxes (S671 090 255)
• Hyundai 040000C90SG	• Bentley PY 112995PA
• Jaguar Fluid 8432 (C2C 8432)	• Maserati 231603

Properties	Unit	Test method
Viscosity at 40° C	29.6 mm <sup>2</sup> /s	DIN 51562
Density at 15° C	0.85 g/ml	DIN 51757
Flash point	200 ° C	DIN ISO 2592

NEW